

TECHNICAL DATA SHEET

Eurovent **COMPRE X**

The pre-compressed tape will expand after installation, increasing its thickness five times. Its basic applications include the installation of gaps and joints in roofs and facades as well as heat and sound insulation. Sealing class > 300 Pa. Flammability class B2.



| CHARACTERISTICS   | NORM            | UNIT                              | VALUE  |
|---|-----------------|-----------------------------------|--|
| Foam base   |                 |                                   | Polyurethane flexible foam                   |
| Basis of impregnation                                   |                 |                                   | Special flame-resistant acrylate             |
| Density   |                 | [kg/m <sup>3</sup> ]              | 85 (±10%)                                    |
| SD-value  | [EN ISO 12572]  | [m]                               | < 0,5  |
| Joint permeability coefficient (a-value), air-tightness | [DIN EN 12114]  | [m <sup>3</sup> / [(h*m*(daPa)n]] | ≤ 1,0  |
| reaction to fire  | [DIN 4102-1]    |                                   | B2   |
| Temperature-change resistance                           | [DIN 18542 BG2] | [°C]                              | - 20 to + 60                                 |
| Application temperature                                 |                 | [°C]                              | +5 to +30                                    |
| Driving rain resistance                                 | [DIN EN 1027]   | [Pa]                              | 300  |
| Colour  |                 |                                   | Black  |
| Size  |                 | [mm x mm x rm]                    | 15 x 30 x 6<br>15 x 40 x 8<br>20 x 50 x 4,3  |
| Box   |                 | [pcs.]                            | 32 for 15/30; 15/40<br>24 for 20/50          |
| Storage   |                 |                                   | 1 year, dry and original packaging at 5-20°C |

**Advantages:**

- High flexibility • Fills joints and crevices • Wind-barrier
- Insulates against wind, cold and moisture

## Eurovent **COMPRE X**

### Application:

Suitable for the installation of windows, doors and garage doors. Moreover, for sealing holes, cracks and grouts in roofs, windows and elevations. It is recommended to protect it against long lasting activity of atmospheric factors. Especially recommended for the insulation of grouts in constructions with a jamb. Insulates against moisture, wind, rain, cold and acoustically.

### Assembly:

When assessing the size that is suitable, a following rule should be obeyed:  $2 \times \text{gap width} = \text{tape width}$ . The gap and the surface to be sealed in particular, should be clean of dust and other dirt. The application of the tape is done by removing protective liner and placing the tape in the gap. In vertical gaps the tape should be applied from the bottom to the top. In horizontal gaps the self-adhesive side of the tape should be positioned at the bottom of the gap. The tape should be applied 2-4mm below the surface plane of the gap. To prevent the roll, that has been unpacked and started, from expanding, the roll should be secured with self-adhesive tape around the diameter.



### Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent-based substances, as they can reduce technical parameters of foil or permanently damage it.

The product is under warranty, providing that the guidelines contained in technical data sheet are being obeyed. We reserve the right to refuse a complaint recognition in case of not following these guidelines.

*Contained information, advice and guidance is given based on our knowledge, researches, experiments and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.*

Product information can be found on the website: [www.eurovent.de](http://www.eurovent.de)

Update date: 09/2020