


TECHNICAL DATA SHEET

Eurovent CLIP NORD-2

Roof tile clip designed for fastening cement and clay roof tiles. Made of hook-profiled steel wire and tipped with rectangular plate crafted from galvanized steel. Suitable for application with a wide variety of roof tiles. Product is resistant to weather conditions.



PARAMETER	UNIT	VALUE
Material		galvanized steel
UV resistance		resistant
Size	[mm x mb]	65 x 20 x 15
Colour		steel
Box weight	[kg]	0,5
Pallet	[pcs]	100

Advantages:

- Fast and easy application
- Protection against shifting
- Reliable installation

Eurovent CLIP NORD-2

Application:

Roof tile clip designed for fastening cement and clay tiles. Fixed by nailing its sharp tip directly into the roof construction and fastening the rectangular plate to the side-lock of the roof tile. Clip ensures reliable installation and helps to resist shifting of roof tiles caused by strong winds.



Storage / transport:

The product should be stored in a dry place, under cover, free from moisture and UV radiation in original undamaged and closed package. Rolls should be transported in covered means of transport. They should be prepared for transport in a manner that protects them from damage and destruction. During transport safety regulations must be observed. The product should be protected from chemical agents, in particular solvent based substances, as they can reduce technical parameters of foil or permanently damage it.

Contained information, advice and guidance is given based on our knowledge, researches, experience and in good faith. We are not responsible for the consequences of improper or incorrect use of our products. Each user of this material will ensure in every possible way, including an examination of the final product in the relevant conditions, the suitability of supplied materials to achieve the objectives pursued by him.

Product information can be found on the website: www.eurovent.de

Update date: 01/2020